

Care and Maintenance

SOSS Invisible Hinges

SOSS[®] invisible hinges are shipped already lubricated and under normal conditions, require no additional care.

If needed, we recommend a spray lubricant, such as WD-40, which serves both as a lubricant and cleaner. Apply gently, taking care not to overspray on the door or frame. Once applied, wipe with a soft cloth.

Don't use cleaning agents, solvents or products like Brasso, because they can damage the finish and/or gum up the hinge links.

The following chemicals are not to be used on any SOSS hinge, closer and power transfer models with nylon links including, but not limited to the model #s: 204, 208, 212, 216, 218, 220, 212IC, 216IC, 218IC, 220IC, 218PT and 220PT:

Acetic acid conc.	Hydrogen sulphide
Acetic acid 10%	Lactic acid 2%
Boric acid 10%	Nitric acid 2%
Calcium chloride 10%	Ozone
Chloroform	Phenol, aqueous
Formic acid 10%	Phosphoric acid 10%
Hydrochloric acid 36%	Potassium permanganate 1%
Hydrochloric acid 2%	Sodium hydroxide solution 5%
Hydrofluoric acid	Sodium hydroxide solution 50%
Hydrogen peroxide 30%	Sulphuric acid 98%
Hydrogen peroxide 0.5%	Tincture of iodine (alc.)

