

GWZQ.R13634 Door Hinges

Page Bottom

Door Hinges

See General Information for Door Hinges

UNIVERSAL INDUSTRIAL PRODUCTS CO

1 COREWAY DR PO BOX 628 PIONEER, OH 43554-0628 USA

Hinge, Series 420* for use on hollow metal, sheet metal and steel covered composite swinging type fire doors rated up to and including 3 hr.

Hinge, Series 220SS, 220AS, 416*, 418* for use on hollow metal, sheet metal and steel covered composite swinging type fire doors rated up to and including 3 hr. Wood/plastic covered composite doors rated up to and including 1-1/2 hr. Also for use on wood core swinging type fire doors rated 20 min.

Hinge, Series 216*, 218*, 220*218PT, 220PT for use on hollow metal, sheet metal, steel covered composite and wood core swinging type fire doors rated 20 min.

Hinge Models 220SS, 220AS, 416, 418 and 420 also Classified in accordance with UL10C.

*Hinge models marked with an asterisk may bear the suffix "SS".

Last Updated on 2017-11-20

<u>Questions?</u>

<u>Print this page</u>

Terms of Use

Page Top

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".

NOW AVAILABLE

R13634